

WHAT IS CLAIMED IS:

1. A serial communication device, comprising:
a serial interface to receive data; and
a direct memory access controller to transfer said data
5 received by said serial interface from said serial interface to
a first memory,
wherein said direct memory access controller is started
up before said serial interface receives said data.
- 10 2. The serial communication device according to claim 1,
wherein said direct memory access controller sets a
number larger than the number of data received at a time as the
number of transfers, and
wherein when the number of data transferred from said
15 serial interface to said first memory reaches said number set
as the number of transfers, said direct memory access
controller outputs a direct memory access transfer end
interrupt signal to a central processing unit.
- 20 3. The serial communication device according to claim 2,
wherein said serial interface outputs a receive timeout
interrupt signal to said central processing unit when said data
reception is stopped for a certain period after the start of
said data reception.
- 25 4. The serial communication device according to claim 3,
wherein said direct memory access controller retransfers
said transferred data from said first memory to a second memory
as triggered by said direct memory access transfer end

interrupt signal or said receive timeout interrupt signal.

5. The serial communication device according to claim 2,
wherein said first memory is comprised of two or more

5 memory areas, and

wherein said direct memory access controller has a
continuous transfer function and transfers said data from said
serial interface to said first memory while alternately
switching the destinations of the data received by said serial
10 interface among said two or more memory areas as triggered by
said direct memory access transfer end interrupt signal or a
receive timeout interrupt signal.